

PRODUCT DATA SHEET

20W-50 SL/CF

Multi-degree four-season motor oil refined in a modern manner and manufactured with high technology by adding package additives selected with care to high quality paraffinic base oils. Used in gasoline-driven engines with turbocharger and catalytic converter; and passenger type cars, pickups and minibus type vehicles with diesel engines.

Properties

- Provides superior protection in all seasons thanks to its high viscosity index.
- Keeps the engine clean with the detergent-dispersant feature of the package additives it is formulated with.
- Decreases oil consumption to a minimum under all kinds of weather and road conditions without foam forming or decrease in fixed oil pressure.
- Decreases maintenance costs and decreases oil consumption to a minimum in old type engines. Provides economy with extended motor oil replacement.

Meets requirements:

- API SL/CF
- ACEA A3/B3

- VW 505 00
- MB-Approval 229.1

TEST	METHOD	TYPICAL PROPERTIES
Density, g/cm3, at 15°C	ASTM D 4052	0,888
Kinematic Viscosity, cSt, at 100°C	ASTM D 445	19.5
Kinematic Viscosity, cSt, at 40°C	ASTM D 445	155
Viscosity Index	ASTM D 2270	128
Flash Point, °C, min	ASTM D 92	240
Pour Point, °C, max	ASTM D 97	-21



20W-50 SL / CF Safety Data Sheet

according to Regulation (EU) 2015/830

Issue date: 21/12/2023 Revision date: 19/11/2024 Supersedes version of: 06/01/2024 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Mixture Trade name : 20W-50 SL/CF Product code : 210004

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Petrol Engine Oil

Uses advised against

No additional information available

Details of the supplier of the safety data sheet

FACO PETROL KİMYA SANAYİ DIŞ TİCARET LTD. ŞTİ.

Center Office: Siteler Mh. 492 Sk. No: 1/A My Vista Smart Aliağa/İZMİR/TÜRKİYE

info@cosmomotoroil.com / www.cosmomotoroil.com

Phone: +90 552 222 6766

Emergency telephone number

Emergency number +90 552 222 6766

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

No labelling applicable

Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

Substance

Not applicable

3.2.	Mixture
------	----------------

3.2. Mixture			
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified, [A complex combination of hydrocarbons obtained from a catalytic dewaxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (Note L)	(CAS No) 64742-70-7 (EC no) 265-174-4 (EC index no) 649-477-00-2 (REACH-no) 01-2119487080-42-0003; 01- 2119487080-42 01-2119484627-25-0025; 01-2119484627-25 01-2119471299-27- 0019; 01-2119471299-27	63	Not classified



-Distillates (petroleum), hydrotreated heavy paraffinic (Note L)	(CAS No) 64742-54-7 (EC no) 265-157-1 (EC index no) 649-467-00-8 (REACH-no) 01-2119484627-25-0025; 01- 2119484627-25 01-2119471299-27-0019; 01-2119471299-27	20	Not classified
Zinc alkyl dithiophosphate	(CAS No) 68649-42-3 (EC no) 272-028-3 (REACH-no) Not available	0.1 - 1	Eye Dam. 1, H318 Aquatic Chronic 2, H411

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3. Full text of H-statements: see section 16

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Take off immediately all contaminated clothing. Wash off immediately with soap and plenty of

water. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact Rinse immediately and plentifully with water, also under the eyelids, for at least 20 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

: Do not induce vomiting. Never give anything by mouth to an unconscious person. Immediately First-aid measures after ingestion

get medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract. May cause drowsiness or dizziness.

: Injection under the skin of pressurized hydrocarbons can cause severe, permanent tissue Symptoms/injuries after skin contact

damage. May cause skin irritation / dermatitis.

: May cause eye irritation. Symptoms/injuries after eye contact

: Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Symptoms/injuries after ingestion

Indication of any immediate medical attention and special treatment needed 4.3.

No additional information available

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media : carbon dioxide (CO2), water, dry chemical powder.

Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : None known. Explosion hazard : None known.

: Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide. Aldehydes. Sulfur oxides.

Hazardous decomposition products in case of

Advice for firefighters

: Cool down the containers exposed to heat with a water spray. Firefighting instructions

: Wear proper protective equipment. In case of fire: Wear self-contained breathing apparatus. Protective equipment for firefighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

: Wear personal protection equipment. Protective equipment

: Evacuate area. Avoid contact with skin, eyes and clothes. **Emergency procedures**

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing. In case of fire: Wear self-contained breathing apparatus.

Evacuate and limit access. Stop leak if safe to do so. Use ventilation/water spray/fog to **Emergency procedures**

disperse vapours. Do not touch spilled material.

Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

Methods and material for containment and cleaning up

For containment : Clean up any spills as soon as possible, using an absorbent material to collect it. For larger spills, dike area and pump into waste containers.

Methods for cleaning up : Collect all waste in suitable and labelled containers and dispose according to local legislation.



6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Handling this product may result in electrostatic accumulation. Use proper grounding

procedures.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Avoid static electricity

discharges. Provide earthing of containers, equipment, pumps and ventilation facilities.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practices. Take off contaminated

clothes. Wash contaminated clothing prior to re-use.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, cool and well-ventilated place.

Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : Either local exhaust or general room ventilation is usually required.

Personal protective equipment : Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.

Materials for protective clothing : Wear suitable protective clothing. Natural fibres (e.g. cotton)

Hand protection : Wear suitable gloves tested to EN374. Thickness of glove material: > 0.13 mm. Break through

time: ≥ 480 min

Eye protection : Use splash goggles when eye contact due to splashing is possible. DIN EN 166

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to

EN140 with Type A/P2 filter or better







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : brown.

Odour Characteristics.

Odour threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available Freezing point : No data available Boiling point : No data available

Flash point : 250 °C

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available
Density : 0.8891 g/mL @ 15°C





Solubility : No data available
Log Pow : No data available
Viscosity, kinematic : 18.8 mm²/s @ 100°C
Viscosity, dynamic : No data available

Explosive properties : Not explosive. However, formation of explosive air/vapour mixtures are possible.

Oxidising properties : not oxidizing.

Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None known under normal conditions of use. No polymerization.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

No hazardous decomposition products known at room temperature.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

-Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rat	> 5000 mg/kg	
LC50 inhalation rat (mg/l)	> 5000 mg/m³	
Skin corrosion/irritation	: Not classified	
Serious eve damage/irritation	· Not classified	

Serious eye damage/irritation : Not classified Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified exposure) : Not classified exposure) : Not classified exposure) : Not classified exposure) : Not classified exposure) : Not classified exposure) : Not classified exposure) : Not classified exposure) : Not classified exposure) : Not classified exposure) : Not classified exposure)

ENOC Protec Premium SL SAE 20W-50

Viscosity, kinematic 18.8 mm²/s @ 100°C

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

Persistence and degradability Inherently biodegradable.

12.3. Bioaccumulative potential

-Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Bioaccumulative potential Bioaccumulative potential.





12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component	
-Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding

versions, covering waste and dangerous waste.

: Can be incinerated according to local regulations.

Waste disposal recommendations : Dispose of this material and its container to hazardous or special waste collection point.

European List of Waste (LoW) code : 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Waste treatment methods

UN-No. (ADR) : Not applicable
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : Not applicable
UN-No. (ADN) : Not applicable
UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

♦ Cosmo



14.6. Special precautions for user

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Other information, restriction and prohibition regulations

: International regulatory information:

AICS: Australia. Inventory of Chemical Substances (AICS) (as amended through 1 September 2015)

CAS RN: 64742-54-7

Name: Distillates, petroleum, hydrotreated heavy paraffinic

Note(s): aU -This entry is a chemical of unknown or variable composition, a complex product of a chemical reaction, or a biological material (UVCB); the Australian inventory denotes this by putting an asterisk (*) after the CAS number.

DSL: Canada. Domestic Substances List (DSL), as amended through September 23, 2015 CAS RN: 64742-54-7

Name: Distillates, petroleum, hydrotreated heavy paraffinic Canada. Categorization of Existing Substances on DSL (September 2006)

CAS RN: 64742-54-7

Name: DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC

Substance category: UORG Meets CEPA criteria: Yes Meets human health criteria: Yes Human health priority: High Meets environmental criteria: No

Persistent: Yes Bioaccumulative: No

Inherently toxic to aquatic organisms: No

Notes: UVCBs-organic

ENCS: not listed

2011)

KECI: Korea. Existing Chemicals Inventory (KECI, January 27, 2015, amended through MoE

2015-95, July 1, 2015)

CAS RN: 64742-54-7

Name: Distillates (petroleum), hydrotreated heavy paraffinic

Korean ID Number: KE-12546

PICCS: Philippines. Inventory of Chemicals and Chemical Substances (PICCS) 2012

CAS RN: 64742-54-7

Name: Distillates (petroleum), hydrotreated heavy paraffinic

TSCA: U.S. Federal, TSCA

TSCA IUR 2006, Partially Exempt Petroleum Process Streams (40 CFR 710.46(b)(1))

CAS RN: 64742-54-7

Name: DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC TSCA CDR, Partially Exempt Petroleum Process Streams (40 CFR 711.6(b)(1)) (September 6,

CAS RN: 64742-54-7

Name: Distillates (petroleum), hydrotreated heavy paraffinic

TSCA High Production Volume (HPV) Chemicals: 1990, 1994 & Post-1994 Additions (01/20/06)

CAS RN: 64742-54-7

Name: DISTILLATES, PETROLEUM, HYDROTREATED HEAVY PARAFFINIC

1990 HPV Challenge Program Chemical

HPV Indicator Value (see notes): 0 Chemical is a candidate for sponsorship under





the HPV Challenge Program

HPV Sponsorship Value (see notes): F Fully Sponsored Chemical

. International regulatory information:

AICS: Australia. Inventory of Chemical Substances (AICS) (as amended through 1 September 2015)

CAS RN: 64742-70-7

Name: Paraffin oils, petroleum, catalytic dewaxed heavy

Note(s): aU This entry is a chemical of unknown or variable composition, a complex product of a chemical reaction, or a biological material (UVCB); the Australian inventory denotes this by putting an asterisk (*) after the CAS number.

DSL: Canada. Domestic Substances List (DSL), as amended through September 23, 2015 CAS RN: 64742-70-7 may be regulated as a member of the Generics group for CAS RN: 8012-95-1

Generics group name: PARAFFIN OILS

Substance category: UORG Meets CEPA criteria: Yes Meets human health criteria: Yes Human health priority: Moderate Meets environmental criteria: No

Persistent: No Bioaccumulative: No

Inherently toxic to aquatic organisms: No

ENCS: not listed

KECI: Korea. Existing Chemicals Inventory (KECI, January 27, 2015, amended through MoE

2015-95, July 1, 2015)

Name: Paraffin oils (petroleum), catalytic dewaxed heavy

Korean ID Number: KE-27774

PICCS: Philippines. Inventory of Chemicals and Chemical Substances (PICCS) 2012

CAS RN: 64742-70-7

Name: Paraffin oils (petroleum), catalytic dewaxed heavy

TSCA: U.S. Federal, TSCA

TSCA IUR 2006, Partially Exempt Petroleum Process Streams (40 CFR 710.46(b)(1))

TSCA CDR, Partially Exempt Petroleum Process Streams (40 CFR 711.6(b)(1)) (September 6,

2011)

CAS RN: 64742-70-7

Name: PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED HEAVY

CAS RN: 64742-70-7 may be regulated as a member of the Generics group for CAS RN: 8012-

95-1

Generics group name: PARAFFIN OILS

TSCA High Production Volume (HPV) Chemicals: 1990, 1994 & Post-1994 Additions (01/20/06) CAS RN: 64742-70-7 may be regulated as a member of the Generics group for CAS RN: 8012-95-1

Generics group name: Paraffin oils

CAS RN: 64742-70-7

Name: Paraffin oils (petroleum), catalytic dewaxed heavy

CAS RN: 64742-70-7

Name: PARAFFIN OILS, PETROLEUM, CATALYTIC DEWAXED HEAVY

1990 HPV Challenge Program Chemical HPV Indicator Value (see notes): 0 HPV Sponsorship Value (see notes): F

Notes: 0 Chemical is a candidate for sponsorship under the HPV Challenge Program; F Fully

Sponsored Chemical.

15.1.2. National regulations

Germany

VwVwS Annex reference

: Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS,

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen

: Zinc alkyl dithiophosphate,-Distillates (petroleum), hydrotreated heavy paraffinic,Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified, [A complex combination of hydrocarbons obtained from a catalytic dewaxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] are listed





SZW-liist van	mutagene	ctoffon
SZVV-IIISL VAIT	mutauene	Stonen

Zinc alkyl dithiophosphate,-Distillates (petroleum), hydrotreated heavy paraffinic,Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified, [A complex combination of hydrocarbons obtained from a catalytic dewaxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting

: None of the components are listed

giftige stoffen - Ontwikkeling

Denmark

Classification remarks

: Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation

: The requirements from the Danish Working Environment Authorities regarding work with

carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

A chemical safety assessment has been carried out for the substance or the mixture by the supplier

SECTION 16: Other information

Other information

: It is the user's responsibility to take the mentioned precautionary measures and to ensure that this information is complete and sufficient for the use of this product. Such information is actually to be best of our knowledge and believes accurate as reliable.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H318	Causes serious eye damage
H411	Toxic to aquatic life with long lasting effects

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

