

PRODUCT DATA SHEET

10W-30 TRACTOR OİL

PRODUCT DEFINITION

TRUCK OİL UTTO 10W30 is a multi-purpose transmission oil blended with high quality solvent refined paraffinic mineral oil containing extreme pressure additives and friction modifiers. It displays excellent lubrication and low noise performance in transmissions, hydraulic systems, oil-immersed wet brakes and power transmissions of agriculture and off-highway equipments.

MEETS REQUIREMENTS

API GL-4; JI CASE: MS 1204-MS 1205-MS 1206-MS 1207-MS 1210; JOHN DEERE: JDM J20C / J20D; NEW HOLLAND: FNHA-2-C201.00; FORD: M2C134-A/B/C/D M2C86-B/C; MASSEY FERGUSON: M1141-M1135-M1143-M1145; WHITE FARM: Q-1826; ALLISON: C-3 / C-4; CATERPILLAR TO-2; VOLVO: WB-101; KUBOTA UDT; EATON VICKERS; ZF-TE-ML 03E/03F/05F/06E/06F/06K/17E/21F

TEST	METHOD	TYPICAL PROPERTIES
Density, g/cm ³ , at 15°C	ASTM D4052	0,87
Kinematic Viscosity, cSt, at 100°C	ASTM D445	10,4
Viscosity Index	ASTM D2270	140
Flash Point, °C, min	ASTM D92	222
Pour Point, °C, max	ASTM D97	-32
Phosphorus % wt.	ASTM D4951	0
Sulfated Ash % wt.	ASTM D874	0,8
HTHS Viscosity., mPa•s @ 150°C,	ASTM D4683	3.0
Total Base Number, mg KOH/g	ASTM D2896	8,5