



## PRODUCT DATA SHEET

# 15W-40 TRAKTOR OIL

## Description

High quality diesel engine oil developed specifically for turbo diesel engines of tractors and combine harvesters.

## Applications

Used for turbo diesel engines of agricultural machines including the latest models.

## Benefits

- Cleans the engine by preventing deposits with the help of detergent-dispersant additives.
- Helps preventing oil consumption and wear.
- Extends oil change intervals.
- Reduces product range in the filo by its wide application area.
- Helps engine to start easily in cold conditions, provides effective lubrication in hot conditions.
- Creates high film layer at high temperatures with its high Viscosity Index modifiers.

## Performance

API CF-4/CF

TEST	METHOD	TYPICAL PROPERTIES
Density, g/cm <sup>3</sup> , at 15°C	ASTM D 4052	0.891
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D445	90
Kinematic Viscosity, cSt, at 100°C	ASTM D 445	12,70
Viscosity Index	ASTM D 2270	154
Flash Point, °C, min	ASTM D 92	235
Pour Point, °C, max	ASTM D 97	-31
Sulfated Ash % wt.	ASTM D874	1,4
Total Base Number, mg KOH/g	ASTM D2896	11,7