

PRODUCT DATA SHEET

20W-50 SL/CF

Multi-degree four-season motor oil refined in a modern manner and manufactured with high technology by adding package additives selected with care to high quality paraffinic base oils. Used in gasoline-driven engines with turbocharger and catalytic converter; and passenger type cars, pickups and minibus type vehicles with diesel engines.

Properties

- Provides superior protection in all seasons thanks to its high viscosity index.
- Keeps the engine clean with the detergent-dispersant feature of the package additives it is formulated with.
- Decreases oil consumption to a minimum under all kinds of weather and road conditions without foam forming or decrease in fixed oil pressure.
- Decreases maintenance costs and decreases oil consumption to a minimum in old type engines. Provides economy with extended motor oil replacement.

Meets requirements:

- API SL/CF
- ACEA A3/B3
- VW 505 00
- MB-Approval 229.1

TEST	METHOD	TYPICAL PROPERTIES
Density, g/cm ³ , at 15°C	ASTM D 4052	0,888
Kinematic Viscosity, cSt, at 100°C	ASTM D 445	19.5
Kinematic Viscosity, cSt, at 40°C	ASTM D 445	155
Viscosity Index	ASTM D 2270	128
Flash Point, °C, min	ASTM D 92	240
Pour Point, °C, max	ASTM D 97	-21