

## PRODUCT DATA SHEET

# 2T Jaso TC

2T is specially designed to provide high performance for use in motorcycles, go-karts and all other two stroke engines. It is used in air or water-cooled two-cycle engines, motorcycles, lawn mowers and agriculture tools. Use fuel/oil ratios as specified by the engine manufacturer up to a maximum of 50:1.

### Properties

- Provides complete protection against soot formation and extends the life of the piston and the piston rings.
- Burns cleaner to reduce deposits and eliminate smoke and engine wear.

### Approvals and Specifications

- API TC
- JASO FB/FC/FD
- ISO-L-EGD/EGB
- GOLBAL GC
- T.I.S.I.

| TEST                                 | METHOD      | TYPICAL PROPERTIES |
|--------------------------------------|-------------|--------------------|
| Density, g/cm <sup>3</sup> , at 15°C | ASTM D 4052 | 0,875              |
| Kinematic Viscosity, cSt, at 100°C   | ASTM D 445  | 9.2                |
| Kinematic Viscosity, cSt, at 40°C    | ASTM D 445  | 66                 |
| Viscosity Index                      | ASTM D 2270 | 110                |
| Flash Point, °C, min                 | ASTM D 92   | 210                |
| Sulfated Ash, % mass                 | ASTM D874   | 0.09               |
| Pour Point, °C, max                  | ASTM D 97   | -18                |