

## PRODUCT DATA SHEET

# 4T 10W40

4T 10W-40 Advanced Multigrade Synthetic Four-Stroke Motorcycle Engine Oil. This product helps to provide an outstanding level of performance in today's high performance motorcycles. It will help keep 4-stroke engines running clean protecting even in extreme operating conditions.

## Properties

- 4T 10W-40 Combines high performance synthetic basestocks and a precisely balanced component system to help provide outstanding engine cleanliness, excellent wear protection at high temperatures and highly effective protection from corrosion.Helps to keep engines clean for smoother operation.
- Provides fuel economy by excellent viscosity control property.
- Shear stable viscosity improvers help resist oil film breakdown.
- Helps to extend engine life
- Long life of critical valve train and bearing components

## Approvals and Specifications

- API SJ
- JASO MA/MA2
- API SL
- API SM
- API SN

TEST	METHOD	TYPICAL PROPERTIES
Density, g/cm <sup>3</sup> , at 15°C	ASTM D 1298	0,85
Kinematic Viscosity, cSt, at 100°C	ASTM D 445	13.6
Kinematic Viscosity, cSt, at 40°C	ASTM D 445	81
Viscosity Index	ASTM D 2270	160
Flash Point, °C, min	ASTM D 92	220
Pour Point, °C, max	ASTM D 97	-30