

## PRODUCT DATA SHEET

### **ATF DEXRON III**

#### **Description:**

High quality paraffinic base oils blended with modern additives obtained by the automatic transmission oil.

#### **Performance Features and Benefits:**

- Oxidation resistance is high; Using long lifetime.
- Contains anti-wear additives.
- Automatic transmission enhances the resistance of parts.
- Rust, corrosion and anti-foam additives include; extends component life
- Heat dissipation is very good; automatic gearbox provides lossless and running smoothly.
- Heat dissipation is very good; automatic gearbox provides lossless and running smoothly.
- Compatible with all sealing elements.

#### **Application:**

Used in automatic and power shift transmissions, torque converters, fluid clutches and certain power steering systems in passenger cars, trucks, excavators and agricultural equipments. Contains red dye for easy identification.

#### **Performance specifications:**

GM DEXRON III D-22247; Allison C-4; Caterpillar TO-2; MB 236.1; MAN 339D(Type V1/Z1); Ford M2C-138-CJ, Ford M2C-166-H, Ford MERCON; ZF TE-ML 02F/03D/04D/11A/14A/17C meet the performance specifications.

#### **Typical Characteristics:**

TEST	METHOD	TYPICAL PROPERTIES
Density, g/cm <sup>3</sup> , at 15°C	ASTM D4052	0,865
Kinematic Viscosity, cSt, at 40°C	ASTM D445	31,3
Kinematic Viscosity, cSt, at 100°C	ASTM D445	7,0
Viscosity Index	ASTM D2270	196
Flash Point, °C, min	ASTM D92	215
Pour Point, °C, max	ASTM D97	-32