

## PRODUCT DATA SHEET

# U-W80 TRACTOR OIL

## PRODUCT DEFINITION

U-tract SAE 80W Tractor Transmission Oil is a premium multi-purpose fluid designed for year-round service in tractor hydraulic systems, transmissions and PTOs, and differentials with wet brake systems. U-tract SAE 80W Tractor Transmission Oil protects against wear and corrosion of tractor components and has excellent friction properties.

## MEETS REQUIREMENTS

ALLISON C3, ALLISON C4API GL-4, Case MAT 3505, FORD M2C-134-A, FORD M2C-134-B, FORD M2C-134-C, FORD M2C-134-D, Ford/NewHolland FNHA-2-C-200.00 (hydraulic oil 134), Ford/NewHolland FNHA-2-C-201.00 (M2C-134D), John Deere J14B, John Deere J14C, John Deere J20A, John Deere J20B, John Deere J20C, John Deere J21A, Komatsu, Kubota UDT, MASSEY FERGUSON M1135, MASSEY FERGUSON M1141, MASSEY FERGUSON M1143, MASSEY FERGUSON M1145, FORD M2C-86-B, FORD M2C-86-C, Steiger SEMS 17001, SAE 80W, Versatile 23M, Versatile 24M, VOLVO VME, White Farm (AGCO) Q-186

TEST	METHOD	TYPICAL PROPERTIES
Density, g/cm <sup>3</sup> , at 15°C	ASTM D4052	886
Kinematic Viscosity, cSt, at 40°C	ASTM D445	58,7
Kinematic Viscosity, cSt, at 100°C	ASTM D445	9,3
Viscosity Index	ASTM D2270	160
Flash Point, °C, min	ASTM D92	>215
Pour Point, °C, max	ASTM D97	-30
TBN (Total base number, mg KOH/g)	ASTM D2896	9,6

## U-TRACT SAE W80 Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 21/12/2023 Revision date: 19/11/2024 Supersedes version of: 06/01/2024

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

**Product Name** Gulf Universal Tractor Transmission Fluid, SAE 80W  
**Product Code(s)** 08102/80W/3

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use** Engine / Hydraulic / Transmission fluid

**Uses advised against** Any other purpose.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier**

### FACO PETROL KİMYA SANAYİ DİŞ TİCARET LTD. ŞTİ.

Center Office: Siteler Mh. 492 Sk. No: 1/A My Vista Smart Aliağa/İZMİR/TÜRKİYE  
info@cosmomotoroil.com / www.cosmomotoroil.com  
Phone: +90 552 222 6766

#### 1.4. Emergency telephone number

2 Phone: +90 552 222 6766

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

**Regulation (EC) No 1272/2008**

<b>Chronic aquatic toxicity</b>	Category 3 - (H412)
---------------------------------	---------------------

Contains Triphenyl phosphite, C14-18 alpha-olefin epoxide, reaction products with boric acid May produce an allergic reaction.

#### 2.2. Label Elements

**Signal word**  
None

#### Hazard statements

H412 - Harmful to aquatic life with long lasting effects

EUH208 - Contains Triphenyl phosphite, C14-18 alpha-olefin epoxide, reaction products with boric acid May produce an allergic reaction.

#### Precautionary Statements - EU (§28, 1272/2008)

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

#### 2.3. Other hazards

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substances / 3.2. Mixtures

This product is a mixture. Health hazard information is based on its ingredients

Chemical name	EC-No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	-	50% - 100%	**	-
Poly long-chain alkyl methacrylate	-	NOT AVAILABLE	2.5% - 10%	Eye Irrit. 2 (H319)	no data available
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	224-235-5	4259-15-8	1% - 2.5%	Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)	01-2119493635-27
Benzene, polypropene derivatives, sulfonated, calcium salts	-	NOT AVAILABLE	1% - 2.5%	Eye Irrit. 2 (H319)	no data available
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	-	1% - 2.5%	Asp. Tox. 1 (H304) (EUH066)	-
C14-18 alpha-olefin epoxide, reaction products with boric acid	-	NOT AVAILABLE	0% - 1%	Skin Sens. 1 (H317)	no data available
Triphenyl phosphite	202-908-4	101-02-0	0% - 1%	Acute Tox. 4 (H302) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) Eye Irrit. 2 (H319) Skin Irrit. 2 (H315) Skin Sens. 1 (H317)	no data available

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. The highly refined base oil may be described by one or more of the following generic CAS identifiers: 64742-54-7, 64742-65-0, 64742-52-5, 64742-53-6, 64742-62-7, 64742-57-0, 64742-01-4, 64741-88-4, 64742-96-4, 64741-97-5, 64742-55-8, 64742-56-9, 64741-89-5, 8042-47-5. See Section 15 for additional information on base oils.

\*\* Substances for which there are Community workplace exposure limits

**Full text of H- and EUH-phrases: see section 16**

### SECTION 4: FIRST AID MEASURES

#### **4.1. Description of first-aid measures**

<b>General advice</b>	May produce an allergic reaction. When symptoms persist or in all cases of doubt seek medical advice.
<b>Inhalation</b>	Move to fresh air.
<b>Skin contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. May cause an allergic skin reaction. If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.
<b>Ingestion</b>	Clean mouth with water. Drink plenty of water. Do not induce vomiting without medical advice.
<b>Protection of First-aiders</b>	Use personal protective equipment. Avoid contact with skin, eyes and clothing.

#### **4.2. Most important symptoms and effects, both acute and delayed**

**Main Symptoms** May cause allergic skin reaction

#### **4.3. Indication of immediate medical attention and special treatment needed**

**Notes to physician** May cause sensitization of susceptible persons. Treat symptomatically.

### **SECTION 5: FIRE FIGHTING MEASURES**

#### **5.1. Extinguishing media**

##### **Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment:., Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

##### **Extinguishing media which shall not be used for safety reasons**

Do not use a solid water stream as it may scatter and spread fire

#### **5.2. Special hazards arising from the substance or mixture**

##### **Special Hazard**

Water runoff can cause environmental damage. Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). In the event of fire and/or explosion do not breathe fumes. This material creates a fire hazard because it floats on water. Combustible material.

##### **Hazardous decomposition products**

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

#### **5.3. Advice for firefighters**

##### **Special protective equipment for fire-fighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

**Advice for non-emergency personnel**

Material can create slippery conditions.

**Advice for emergency responders**

For personal protection see section 8.

## 6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

## 6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills.

## 6.4. Reference to other sections

See Section 8/12/13 for additional information

# SECTION 7: HANDLING AND STORAGE

## 7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use.

## 7.2. Conditions for safe storage, including any incompatibilities

### Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

### Incompatible materials

Oxidizing agent

## 7.3. Specific end uses

### Recommended Use

Engine / Hydraulic / Transmission fluid

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

### Exposure limits

#### Legend

TWA - Time-Weighted Average; STEL - Short Term Exposure Limit; Ceiling - Ceiling Value

Chemical name	European Union	United Kingdom	France	Spain
Highly refined base oil (Viscosity >20.5 cSt @40°C)				VLA-EC: 10 mg/m <sup>3</sup> VLA-ED: 5 mg/m <sup>3</sup>
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)				VLA-EC: 10 mg/m <sup>3</sup> VLA-ED: 5 mg/m <sup>3</sup>

Spain Límites de Exposición Profesional Para Agentes Químicos en España (Ley 31/1995).

Chemical name	Germany	Italy	Portugal	Netherlands
Highly refined base oil (Viscosity >20.5 cSt @40°C)		TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)		TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	

Italy Istituto Superiore per la Prevenzione e la Sicurezza del Lavoro (ISPESL), Allegato XXXVIII e Allegato XLIII - Valori Limite di Esposizione Professionale.

Portugal Valores-limite e índices biológicos de exposição profissional a agentes químicos. Quadro 1 - Valores Limite de Exposição (Norma Portuguesa NP 1796:2014).

Chemical name	Austria	Switzerland	Poland	Ireland
Highly refined base oil (Viscosity >20.5 cSt @40°C)				STEL: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> (Mist)
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)				STEL: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> (Mist)

Ireland 2016 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001.

Chemical name	Finland	Denmark	Norway	Sweden
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5mg/m <sup>3</sup> (Öljysumu)	TWA: 1 mg/m <sup>3</sup> (Olietäge)	TWA: 1 mg/m <sup>3</sup> (Oljetäke)	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup> (Oljedimma)
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5mg/m <sup>3</sup> (Öljysumu)	TWA: 1 mg/m <sup>3</sup> (Olietäge)	TWA: 1 mg/m <sup>3</sup> (Oljetäke)	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup> (Oljedimma)

Finland Förrdningen om koncentrationer som befunnits skadliga, 268/2014 - HTP-arvot 2014.

Denmark Bekendtgørelse om grænseværdier for stoffer og materialer. Arbejdstilsynets bekendtgørelse nr. 507 Bilag 2 Afsnit A.

Norway Forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (Forskrift om tiltaks- og grenseverdier), FOR-2011-12-06-1358, FOR-2016-06-21-760, FOR-2016-12-22-1860.

Sweden Arbetsmiljöverkets föreskrifter om hygieniska gränsvärden och allmänna råd om tillämpningen av föreskrifterna.

Chemical name	Czech Republic	Hungary	Bulgaria	Romania
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup> Ceiling: 10 mg/m <sup>3</sup>		TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup> Ceiling: 10 mg/m <sup>3</sup>		TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>

Czech Republic Narizeni vlady 93/2012, kterym se meni narizeni vlady c.361/2007 Sb., kterym se stanoví podmínky ochrany zdraví při práci, ve znění narizeni vlady c.68/2010 Sb.

Bulgaria НАРЕДБА #13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа.

Romania Valori Limit Obligatorii Nationale de expunere profesională ale agenților chimic - Anex Nr.1 Publicat în Monitorul Oficial, Partea I nr. 845.

Chemical name	Greece	Cyprus	Turkey	Malta
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup>			
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup>			

Greece Οριακές Τιμές Επαγγελματικής Έκθεσης - Προστασία της υγείας και της ασφάλειας των εργαζομένων που εκτίθενται σε ορισμένους καρκινογόνους και μεταλλαξιογόνους παράγοντες 127/2000.

Chemical name	Belgium	Luxembourg	Iceland	Croatia
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>			
Highly refined, low viscosity	TWA: 5 mg/m <sup>3</sup>			

mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	STEL: 10 mg/m <sup>3</sup>			
--	----------------------------	--	--	--

*Belgium Arrêté royal relatif à la protection de la santé et de la sécurité des travailleurs contre les risques liés à des agents chimiques sur le lieu de travail.*

Chemical name	Russia	Estonia	Latvia	Lithuania
Highly refined base oil (Viscosity >20.5 cSt @40°C)			TWA: 5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup>
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)			TWA: 5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup>
Triphenyl phosphite	MAC: 0.1 mg/m <sup>3</sup> (s)			

*Russia ГН 2.2.5.1313-03 "Гигиенические нормативы. Предельно допустимые концентрации (ПДК) вредных веществ в воздухе рабочей зоны".*

*Latvia Ministru Kabineta noteikumi Nr. 325 - Darba aizsardzības prasības, saskaroties ar ķīmiskajām vielām darba vietās.*

*Lithuania Del Lietuvos higienos normos HN 23:2011 "Cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai".*

Chemical name	Belarus	Ukraine	Slovakia	Slovenia
Highly refined base oil (Viscosity >20.5 cSt @40°C)			TWA: 5mg/m <sup>3</sup>	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)			TWA: 5mg/m <sup>3</sup>	
Triphenyl phosphite	(s)			

*Belarus Санитарные нормы, правила и гигиенические нормативы "Перечень регламентированных в воздухе рабочей зоны вредных веществ".*

*Slovakia Nariadenie vlády Slovenskej republiky z 16. januára 2002 o ochrane zdravia pri práci s karcinogénnymi a mutagénymi faktormi.*

## Derived No Effect Level (DNEL)

### Workers Systemic toxicity

Chemical name	Long term - Oral exposure	Long term - Dermal exposure	Long term - Inhalation exposure	Short term - Oral Exposure	Short term - Dermal exposure	Short term - Inhalation exposure
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)		9.6 mg/kg	6.6 mg/m <sup>3</sup>			
Triphenyl phosphite		0.3 mg/kg	1.06 mg/m <sup>3</sup>			

### Workers Local effects

Chemical name	Long term - Oral exposure	Long term - Dermal exposure	Long term - Inhalation exposure	Short term - Oral Exposure	Short term - Dermal exposure	Short term - Inhalation exposure
Triphenyl phosphite		11.7 µg/cm <sup>2</sup>			11.7 µg/cm <sup>2</sup>	

### Consumers Systemic toxicity

Chemical name	Long term - Oral exposure	Long term - Dermal exposure	Long term - Inhalation exposure	Short term - Oral Exposure	Short term - Dermal exposure	Short term - Inhalation exposure
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	0.19 mg/kg	4.8 mg/kg	1.67 mg/m <sup>3</sup>			
Triphenyl phosphite	75 µg/kg	150 µg/kg	0.53 mg/m <sup>3</sup>			



## Consumers Local effects

Chemical name	Long term - Oral exposure	Long term - Dermal exposure	Long term - Inhalation exposure	Short term - Oral Exposure	Short term - Dermal exposure	Short term - Inhalation exposure
Triphenyl phosphite		11.7 µg/cm <sup>2</sup>			11.7 µg/cm <sup>2</sup>	

## Predicted No Effect Concentration (PNEC)

Chemical name	Fresh water	Sea water	Fresh water sediment	Sea sediment	Soil
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	4 µg/L	4.6 µg/L	0.0701 mg/kg	0.00701 mg/kg	0.0548 mg/kg

## 8.2. Exposure controls

### Engineering Measures

Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

Engineering controls should be considered as the first line of protection against adverse exposure to harmful substances. Administrative controls and PPE should be used in the absence of engineering controls or as supplemental controls where engineering controls are insufficient in reducing specific exposures to an acceptable level.

### Eye Protection

Safety glasses with side-shields.

### Hand Protection

The following glove type may be suitable for handling this product: Protective gloves complying with EN 374.

#### Nitrile rubber

Glove thickness => 0.38 mm Break through time => 480 min

#### Butyl rubber

Glove thickness => 0.64 mm Break through time => 480 min

Glove material suitability will vary depending on specific use conditions. Consideration should be given to variables such as operational characteristics, anticipated contact time, task requirements and other factors relevant to the selection of PPE. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Any specific glove information provided is based on published literature and glove manufacturer data. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

### Skin and body protection

Long sleeved clothing.

### Respiratory protection

No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

*This information is based on the state in which the specific product is delivered and on the intended use specified within this SDS. This information is provided based on literature reference, manufacturer specifications and recommendations and/or derived by analogy with similar substances. The level of protection and types of exposure controls will vary depending on potential exposure conditions.*

### Hygiene measures

Regular cleaning of equipment, work area and clothing is recommended. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

### Environmental Exposure Controls

Do not allow material to contaminate ground water system.

### Thermal hazards

None under normal use conditions



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Physical state	liquid	Appearance	clear amber
Odor	Hydrocarbon-like	Odor threshold	Not Determined
Property	Values	Remarks	
pH	Not Determined		
Melting point / freezing point	Not Determined		
Boiling point / boiling range	Not Determined		
Flash point	224 °C / 435 °F	ASTM D 92	
Evaporation rate	Not Determined		
Flammability (solid, gas)	Not Determined		
Flammability Limit in Air			
Upper flammability limit:	Not Determined		
Lower flammability limit:	Not Determined		
Vapor pressure	Not Determined		
Vapor density	Not Determined		
Relative density	0.8848	@15°C	
Solubility(ies)	Insoluble in water		
Partition coefficient	Not Determined		
Autoignition temperature	Not Determined		
Decomposition temperature	Not Determined		
Kinematic viscosity	58.1 cSt @ 40 °C	ASTM D 445	
Explosive properties	Not applicable		
Oxidizing Properties	Not applicable		

### 9.2. Other information

Viscosity, kinematic (100°C)	9.42 cSt @ 100°C	ASTM D 445
Pour Point	-42 °C / -44 °F	ASTM D 97
VOC Content (ASTM E-1868-10)	Not Determined	
VOC content	Not Determined	

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None under normal use conditions

### 10.2. Chemical stability

Stable under normal conditions

### 10.3. Possibility of hazardous reactions

None under normal use conditions

### 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition, Extremes of temperature and direct sunlight

### 10.5. Incompatible materials

Oxidizing agent

### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### Product Information - Principle Routes of Exposure

Inhalation	None known
Eye contact	None known
Skin contact	Repeated or prolonged skin contact may cause allergic reactions with susceptible persons
Ingestion	None known

#### Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known or supplied information.

#### Acute toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	= 3100 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Triphenyl phosphite	= 444 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 6.7 mg/L ( Rat ) 1 h

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

#### Sensitization

##### Respiratory Sensitization

Based on available data, the classification criteria are not met.

##### Skin sensitization

Repeated contact may cause allergic reactions in very susceptible persons.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### Specific target organ systemic toxicity (single exposure)

Based on available data, the classification criteria are not met

#### Specific target organ systemic toxicity (repeated exposure)

Based on available data, the classification criteria are not met

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

#### Aquatic toxicity

H412 - Harmful to aquatic life with long lasting effects

Chemical name	Algae/aquatic plants	Fish	Crustacea
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>100: 72 h mg/L	>100: 96 h mg/L	>100: 48 h mg/L
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	1.0 - 5.0: 96 h Pseudokirchneriella subcapitata mg/L EC50	10.0 - 35.0: 96 h Pimephales promelas mg/L LC50 semi-static 1.0 - 5.0: 96 h Pimephales promelas mg/L LC50 static	1 - 1.5: 48 h Daphnia magna mg/L EC50
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>100: 72 h mg/L	>100: 96 h mg/L	>100: 48 h mg/L

### 12.2. Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

### 12.3. Bioaccumulative potential

Chemical name	Partition coefficient
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	2.86
Triphenyl phosphite	4.98

### 12.4. Mobility

The product is insoluble and floats on water

### 12.5. Results of PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

### 12.6. Other adverse effects

None known

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### Waste from Residues / Unused Products

Dispose of in accordance with local regulations

#### Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Observe all label precautions until container is cleaned, reconditioned or destroyed.

#### Other Data

According to the European Waste Catalog, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: TRANSPORT INFORMATION

**14.1. UN-Number**

Not regulated

**14.2. UN proper shipping name**

Not regulated

**14.3. Transport hazard class**

Not regulated

**14.4. Packing Group**

Not regulated

**14.5. Environmental Hazards**

None

**14.6. Special precautions for users**

None

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

**IMDG** Not regulated

**ADR** Not regulated

**IATA** Not regulated

**ADN** Not regulated

## SECTION 15: REGULATORY INFORMATION

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008)  
Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)  
European Agreement concerning the International Carriage of Dangerous Goods by Road  
Safety Data Sheet according to Regulation EC 1907/2006 (REACH) with its amendment regulation EC 2015/830  
European Agreement concerning the International Carriage of Dangerous Goods by Road/ Regulations concerning the International Carriage of Dangerous Goods by Rail  
International Civil Aviation Organization / International Air Transport Association Dangerous Goods Regulation

**Substance(s) of Very High Concern**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59).

**Authorizations and/or restrictions on use:**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII). This product does not contain substances subject to authorization (Regulation (EC) No. 1907/2006 (REACH), Annex XIV).

#### **National regulations**

##### **Germany WGK Classification**

Low hazard to water/Class 1

##### **Product Registration number**

Denmark Registration (DK)

No information available

#### **International Regulations**

##### **Ozone-depleting substances (ODS)**

Not applicable

##### **Persistent Organic Pollutants**

Not applicable

##### **Chemicals Subject to Prior Informed Consent (PIC)**

Not applicable

#### **International Inventories**

##### **TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

All ingredients are on the inventory or exempt from listing

##### **DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

All ingredients are on the inventory or exempt from listing

##### **AICS** - Australian Inventory of Chemical Substances

All ingredients are on the inventory or exempt from listing

##### **PICCS** - Philippines Inventory of Chemicals and Chemical Substances

All ingredients are on the inventory or exempt from listing

##### **KECL** - Korean Existing and Evaluated Chemical Substances

All ingredients are on the inventory or exempt from listing

##### **IECSC** - China Inventory of Existing Chemical Substances

All ingredients are on the inventory or exempt from listing

##### **ENCS** - Japan Existing and New Chemical Substances

All ingredients are on the inventory or exempt from listing

##### **TCSI** - Taiwan National Existing Chemical Inventory

Contact supplier for inventory compliance status

##### **NZIoC** - New Zealand Inventory of Chemicals

All ingredients are on the inventory or exempt from listing

#### **Other Information**

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

V

Chemical name	CAS No	EC-No	REACH Registration Number
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487081-40-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4	01-2119487080-42-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx
White mineral oil (petroleum)	8042-47-5	232-455-8	

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical name	CAS No	EC-No	REACH Registration Number
Distillates (petroleum), hydrotreated heavy paraffinic	63742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487067-30-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	500-183-1	01-2119486452-34-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx



## 15.2. Chemical Safety Assessment

A chemical safety assessment according to regulation (EC) No. 1907/2006 is not required

## SECTION 16: OTHER INFORMATION

### Key or legend to abbreviations and acronyms used in the safety data sheet

Repr.-Reproduction toxicity  
 Asp. Tox. - Aspiration Toxicity  
 Acute Tox. - Acute Toxicity  
 Aquatic Acute - Acute Aquatic Toxicity  
 Aquatic Chronic - Chronic Aquatic Toxicity  
 Eye Dam. - Eye Damage  
 Eye Irrit. - Eye Irritation  
 Skin Corr. - Skin Corrosion  
 Skin Irrit. - Skin Irritation  
 Skin Sens. - Skin Sensitizer  
 Resp. Sens. - Respiratory Sensitizer  
 STOT SE - Specific target organ systemic toxicity (Single exposure)  
 STOT RE - Specific target organ systemic toxicity (repeated exposure)  
 VOC - Volatile organic compounds

### Full text of H-Statements which may be referred to under Sections 2 and 3

<ul style="list-style-type: none"> <li>• H224 - Extremely flammable liquid and vapor</li> <li>• H225 - Highly flammable liquid and vapor</li> <li>• H226 - Flammable liquid and vapor</li> <li>• H270 - May cause or intensify fire; oxidizer</li> <li>• H271 - May cause fire or explosion; strong oxidizer</li> <li>• H272 - May intensify fire; oxidizer</li> <li>• H290 - May be corrosive to metals</li> <li>• H300 - Fatal if swallowed</li> <li>• H301 - Toxic if swallowed</li> <li>• H302 - Harmful if swallowed</li> <li>• H304 - May be fatal if swallowed and enters airways</li> <li>• H310 - Fatal in contact with skin</li> <li>• H311 - Toxic in contact with skin</li> <li>• H312 - Harmful in contact with skin</li> <li>• H314 - Causes severe skin burns and eye damage</li> <li>• H315 - Causes skin irritation</li> <li>• H317 - May cause an allergic skin reaction</li> <li>• H318 - Causes serious eye damage</li> <li>• H319 - Causes serious eye irritation</li> <li>• H330 - Fatal if inhaled</li> <li>• H331 - Toxic if inhaled</li> <li>• H332 - Harmful if inhaled</li> <li>• H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled</li> <li>• H335 - May cause respiratory irritation</li> <li>• H336 - May cause drowsiness or dizziness</li> <li>• H340 - May cause genetic defects</li> </ul>	<ul style="list-style-type: none"> <li>• H341 - Suspected of causing genetic defects</li> <li>• H350 - May cause cancer</li> <li>• H351 - Suspected of causing cancer</li> <li>• H360 - May damage fertility or the unborn child</li> <li>• H361 - Suspected of damaging fertility or the unborn child</li> <li>• H362 - May cause harm to breast-fed children</li> <li>• H370 - Causes damage to organs</li> <li>• H371 - May cause damage to organs</li> <li>• H372 - Causes damage to organs through prolonged or repeated exposure</li> <li>• H373 - May cause damage to organs through prolonged or repeated exposure</li> <li>• H400 - Very toxic to aquatic life</li> <li>• H410 - Very toxic to aquatic life with long lasting effects</li> <li>• H411 - Toxic to aquatic life with long lasting effects</li> <li>• H412 - Harmful to aquatic life with long lasting effects</li> <li>• H413 - May cause long lasting harmful effects to aquatic life</li> <li>• H360Df - May damage the unborn child. Suspected of damaging fertility</li> <li>• H360D - May damage the unborn child</li> <li>• H360FD - May damage fertility. May damage the unborn child</li> <li>• H360F - May damage fertility</li> <li>• H361d - Suspected of damaging the unborn child</li> <li>• H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child</li> <li>• H361f - Suspected of damaging fertility</li> <li>• EUH066 - Repeated exposure may cause skin dryness or cracking</li> <li>• EUH210 - Safety data sheet available on request</li> <li>• EUH208 - May produce an allergic reaction</li> </ul>
---	--

### Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

Physical hazards	On basis of test data
Health Hazards	Calculation Method
Environmental Hazards	Calculation Method



